



**MAX 98.6% EFFICIENCY**

**IP65 PROTECTION**



## Safe & Reliable

- High reliability due to good heat dissipation design
- IP65, wider working temperature and altitude, adapt to various installation environments
- Integrated lightning protection for both DC and AC
- Adapt to complex power grid
- High anti-corrosion ability with aluminum alloy die casting technology



## High Revenue

- High yield with Max. 98.6% efficiency
- European weighted efficiency 98.2%
- Longer working hours due to the lower start-up voltage and wider MPPT range
- Up to 10% continuous output overloading capacity
- Dual MPPT design with precise MPPT algorithm
- Standard 5 years warranty, extendable to 10 or 15 years



## Easy to use

- Compact elegant design, less than 25kg, easy for installation
- Support wireless and wired internet connection (RS485/Wi-Fi/GPRS/LAN optional)
- Remote upgrading available
- Intelligent positioning abnormal string with integrated I/V scan function

# TECHNICAL PARAMETERS THREE PHASE:RCM-4-TP/5-TP/6-TP/8-TP/10-TP/12-TP/15-TP/17-TP/20-TP/25-TP

Model	RCM-4-TP	RCM-5-TP	RCM-6-TP	RCM-8-TP	RCM-10-TP	RCM-12-TP	RCM-15-TP	RCM-17-TP	RCM-20-TP	RCM-25-TP
<b>Input</b>										
Max. Input Power (W)	5,200	6,500	7,800	10,400	13,000	15,600	19,500	22,100	26,000	32,500
Start-up Voltage (V)	200	200	200	200	200	200	200	200	200	200
Min. DC Voltage (V)	150	150	150	150	150	150	150	150	150	150
Max. DC Input Voltage (V)	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100
Rated DC Input Voltage (V)	620	620	620	620	620	620	620	620	620	620
MPPT Voltage Range (V)	200-950	200-950	200-950	200-950	200-950	200-950	200-950	200-950	200-950	200-950
No. of MPP Trackers	2	2	2	2	2	2	2	2	2	2
No. of DC Inputs per MPPT	1/1	1/1	1/1	1/1	1/1	1/1	1/2	2/2	2/2	2/2
Max. Input Current (A)	11/11	11/11	11/11	11/11	11/11	11/11	11/22	22/22	22/22	22/22
Max. Short-circuit Current (A)	15/15	15/15	15/15	15/15	15/15	15/15	15/30	30/30	30/30	30/30
<b>Output</b>										
Rated Output Power (kW)	4	5	6	8	10	12	15	17	20	25
Max. Output Power (kW)	4.4	5.5	6.6	8.8	11	13.2	16.5	18.7	22	25
Max. Apparent Power (kVA)	4.4	5.5	6.6	8.8	11	13.2	16.5	18.7	22	25
Rated Output Voltage (V)	3L/N/PE, 230/400V									
Rated AC Frequency (Hz)	50/60Hz 45-55Hz/55-65Hz									
Max. Output Current (A)	6.7	8.4	10	13.3	16.5	20	25	28.4	31.9	39
Power Factor	0.8 leading ...0.8 lagging									
Max. Total Harmonic Distortion	< 3% @Rated Output Power									
DCI	< 0.5%In									
<b>Efficiency</b>										
Max. Efficiency	98.1%	98.1%	98.3%	98.3%	98.6%	98.6%	98.6%	98.6%	98.6%	98.6%
European Efficiency	97.9%	97.9%	98.0%	98.0%	98.2%	98.2%	98.2%	98.2%	98.2%	98.2%
MPPT Efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%
<b>Protection</b>										
DC Reverse Polarity Protection	Integrated									
Insulation Resistance Protection	Integrated									
DC Switch	Optional									
Surge Protection	Integrated ( Type II )									
Over-temperature Protection	Integrated									
Residual Current Protection	Integrated									
Anti-islanding Protection	Integrated									
AC Short-circuit Protection	Integrated									
AC Over-voltage Protection	Integrated									
<b>General Data</b>										
Dimensions (mm)	550W*410H*175D									
Weight (kg)	22					25				
Protection Degree	IP65									
Self-consumption at Night (W)	< 1									
Topology	Transformer-less									
Operating Temperature Range (° C)	-30-60									
Relative Humidity	0~100%									
Operating Altitude (m)	4000 (derating@ > 3000)									
Cooling	Natural Convection					Smart Fan Cooling				
Noise Level (dB)	< 25					< 40				
Display	OLED & LED									
Communication	RS485/WiFi/GPRS/LAN (Optional)									
Compliance	NB/T32004, IEC62109, IEC62116, VDE4105, VDE0126, UTE C15-712-1, AS4777, C10/11, CEI0-21, RD1699, NBR16149, IEC61727, IEC60068, IEC61683, EN50549, EN61000									