

BIFACIAL N-TYPE MONO CRYSTALLINE HALF CUT MODULE – DOUBLE GLASS

550 / 555 / 560 / 565 / 570 / 575 / 580 Watts

Lynx Series



Overview

N-type solar cells (TOPCon) are seen as the technology of the future. N-type (TopCon) technology guarantees high performance and low degradation of the PV module, substantially improving the results and the yield in the time. "Lynx" Series module is the ideal solution for end users who want a Quality PV & reliable product over time and a fast turnaround on their investments.

Key Benefits

	Zero light induced Degradation		30 Years Limited Product Warranty
	Higher yield per surface area		Low Pmax Temperature Coefficient
	Low LCOE		Higher Light Conversion



Guaranteed mechanical resistance to severe weather conditions



Positive Tolerance




100 % electro-luminescence tested

Tests, Certifications and Warranties

Standard Tests	IEC 61215, IEC 61730
Factory Quality Tests	ISO 9001: 2015, ISO 14001: 2015
Certifications	Conformity to CE, PV CYCLE Fire safety Class C according to UL790
Insurance	Third party liability insurance provided by Liberty Mutual
Wind and Snow Loads Testing	Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal)
Withstanding Hail	Maximum Diameter of 25 mm with impact speed of 23 m/s
Power Tolerance	Guaranteed +0/+5W (STC condition)
Warranties	<ul style="list-style-type: none"> • 30-year limited product warranty • 15-year manufacturer warranty on 93.40% of the nominal performance • 30-year transferable linear power output warranty

Linear Performance Warranty



First Year Output $\geq 99.0\%$ 2-30 Year Decline $\leq 0.40\%$ 30 Year Output $\geq 87.40\%$

Lynx

BIFACIAL N-TYPE MONO CRYSTALLINE HALF CUT MODULE – DOUBLE GLASS

RCM-xxx-7DBNF (xxx=550-580)

Electrical Characteristics

POWER CLASS ⁽¹⁾		550		555		560		565		570		575		580	
Testing Condition		STC ⁽²⁾	NMOT ⁽³⁾	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power	P _{max} [Wp]	550	413	555	417	560	421	565	425	570	429	575	433	580	436
Maximum Power Voltage	V _{mp} [V]	41.50	38.99	41.64	39.12	41.77	39.25	41.92	39.38	42.07	39.51	42.22	39.60	42.37	39.69
Maximum Power Current	I _{mp} [A]	13.26	10.60	13.33	10.67	13.41	10.73	13.48	10.79	13.55	10.85	13.62	10.92	13.69	10.99
Open Circuit Voltage	V _{oc} [V]	50.21	47.70	50.34	47.82	50.47	47.94	50.60	48.06	50.74	48.20	50.88	48.32	51.06	48.44
Short Circuit Current	I _{sc} [A]	14.00	11.29	14.07	11.35	14.15	11.42	14.23	11.49	14.31	11.55	14.39	11.62	14.46	11.69
Module Efficiency	Eff [%]	21.29		21.48		21.68		21.87		22.07		22.26		22.45	
Maximum Series Fuse	IR [A]	30													
Maximum System Voltage	V _{sys} [V]	1500V DC													

(1) Measurement Tolerances: P_{max} (± 3%), I_{sc} & V_{oc} (± 3%) - Power Classification 0/+5W

(2) STC (Standard Testing Condition): Irradiance 1000W/m², Cell Temperature 25°C, AM 1.5

(3) NMOT (Nominal Operating Module Temperature): Irradiance 800W/m², NMOT, Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s

Bi Facial Output (4)


POWER CLASS		550		555		560		565		570		575		580	
		P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]
Power with Backside Gain	+5 [%]	577,5	22,4%	582,8	22,6%	588,0	22,8%	593,3	23,0%	598,5	23,2%	603,8	23,4%	609,0	23,6%
	+10 [%]	605,0	23,4%	610,5	23,6%	616,0	23,8%	621,5	24,1%	627,0	24,3%	632,5	24,5%	638,0	24,7%
	+15 [%]	632,5	24,5%	638,3	24,7%	644,0	24,9%	649,8	25,2%	655,5	25,4%	661,3	25,6%	667,0	25,8%
	+20 [%]	660,0	25,5%	666,0	25,8%	672,0	26,0%	678,0	26,2%	684,0	26,5%	690,0	26,7%	696,0	26,9%
	+25 [%]	687,5	26,6%	693,8	26,9%	700,0	27,1%	706,3	27,3%	712,5	27,6%	718,8	27,8%	725,0	28,1%
	+30 [%]	715,0	27,7%	721,5	27,9%	728,0	28,2%	734,5	28,4%	741,0	28,7%	747,5	28,9%	754,0	29,2%

(4) Bifaciality Factor > 80% - Back-side power gain depends upon the specific project albedo - Efficiency is according to the surface of the module

Mechanical Data

Dimensions	2278 mm x 1134 mm x 30 mm
Weight	32,2 Kg
Cell Type	N-Type TOPCon- 182mm x 91mm (2 x 72 Pcs) - M10
Front Glass	2.0 mm Tempered and low iron glass + ARC
Rear Side	2.0 mm Tempered and low iron glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68, 3 Bypass diodes
Connector	MC4 compatible
Output cable	4mm ² - Length: 350 mm or customized

Dimensions




RECOM assumes no liability or responsibility for any typographical error, layout error, misinformation, any other error, omission, contained herein.

www.recom-tech.com

I-V Curve

The module relative power loss at low light irradiance of 200W/m² is less than 3%.



Temperature Characteristics

P _{max} Temperature Coefficient	-0.290% / °C
V _{oc} Temperature Coefficient	-0.250% / °C
I _{sc} Temperature Coefficient	+0.045% / °C
Operating Temperature	-40~+85 °C
Nominal Operating Module Temperature (NMOT)	42 ± 2 °C

Packing Configuration

Container	40' HC
Pieces per Pallet	37
Pallets per Container	20
Pieces per Container	(37+37) x 10 = 740 pcs

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to on-going innovation, research and product enhancement, RECOM Technologies reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein. Please read the safety and installation instructions before using the modules.