

## BIFACIAL N-TYPE MONO CRYSTALLINE HALF CUT MODULE - DOUBLE GLASS

610 / 615 / 620 / 625 / 630 / 635 Watts

# Lynx Series



### Overview

N-type solar cells (TOPCon) are seen as the technology of the future. N-type (TopCon) technology guarantees high performance and low degradation of the PV module, substantially improving the results and the yield in the time. "Lynx" Series module is the ideal solution for end users who want a Quality PV & reliable product over time and a fast turnaround on their investments.

### Key Benefits

	Zero light induced Degradation		30 Years Limited Product Warranty
	Higher yield per surface area		Low Pmax Temperature Coefficient
	Low LCOE		Higher Light Conversion



Guaranteed mechanical resistance to severe weather conditions



Positive Tolerance




100 % electro-luminescence tested

### Tests, Certifications and Warranties

Standard Tests	IEC 61215, IEC 61730
Factory Quality Tests	ISO 9001: 2015, ISO 14001: 2015
Certifications	Conformity to CE, PV CYCLE Fire safety Class C according to UL790
Wind and Snow Static Loads	Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal)
Withstanding Hail	Maximum Diameter of 25 mm with impact speed of 23 m/s
Power Tolerance	Guaranteed +0/+5W (STC condition)
Warranties	<ul style="list-style-type: none"> <li>• 30-year limited product warranty</li> <li>• 15-year manufacturer warranty on 93.40% of the nominal performance</li> <li>• 30-year transferable linear power output warranty</li> </ul>

### Linear Performance Warranty



First Year Output **≥ 99.0%**    2-30 Year Decline **≤ 0.40%**    30 Year Output **≥ 87.40%**

Lynx

**BIFACIAL N-TYPE MONO CRYSTALLINE HALF CUT MODULE - DOUBLE GLASS**

RCM-xxx-7DBNN (xxx=610-635)

**Electrical Characteristics**

POWER CLASS <sup>(1)</sup>			610		615		620		625		630		635	
Testing Condition			STC <sup>(2)</sup>	NMOT <sup>(3)</sup>	STC	NMOT								
Maximum Power	Pmax	[Wp]	610	462,30	615	466,00	620	469,70	625	473,30	630	477,10	635	480,80
Maximum Power Voltage	Vmp	[V]	45,70	42,80	45,90	43,00	46,10	43,20	46,30	43,40	46,50	43,60	46,70	43,70
Maximum Power Current	Imp	[A]	13,35	10,80	13,40	10,84	13,45	10,87	13,50	10,91	13,55	10,95	13,60	10,99
Open Circuit Voltage	Voc	[V]	55,10	52,00	55,30	52,20	55,50	52,40	55,70	52,60	55,90	52,80	56,10	53,00
Short Circuit Current	Isc	[A]	14,11	11,39	14,16	11,43	14,21	11,47	14,26	11,51	14,31	11,55	14,36	11,59
Module Efficiency	Eff	[%]	21,82		22,00		22,18		22,36		22,54		22,72	
Maximum Series Fuse	IR	[A]	30											
Maximum System Voltage	VSYS	[V]	1500V DC											

(1) Measurement Tolerances: Isc & Voc (± 3%) - Power Classification 0/+5W  
 (2) STC (Standard Testing Condition): Irradiance 1000W/m², Cell Temperature 25°C, AM 1.5  
 (3) NMOT (Nominal Operating Module Temperature): Irradiance 800W/m², NMOT, Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s

**Bi Facial Output (4)**

POWER CLASS			610		615		620		625		630		635	
Power with Backside Gain			Pmax [Wp]	Eff [%]										
	+5	[%]	640,5	22,9%	645,8	23,1%	651,0	23,3%	656,3	23,5%	661,5	23,7%	666,8	23,9%
	+10	[%]	671,0	24,0%	676,5	24,2%	682,0	24,4%	687,5	24,6%	693,0	24,8%	698,5	25,0%
	+15	[%]	701,5	25,1%	707,3	25,3%	713,0	25,5%	718,8	25,7%	724,5	25,9%	730,3	26,1%
	+20	[%]	732,0	26,2%	738,0	26,4%	744,0	26,6%	750,0	26,8%	756,0	27,0%	762,0	27,3%
	+25	[%]	762,5	27,3%	768,8	27,5%	775,0	27,7%	781,3	27,9%	787,5	28,2%	793,8	28,4%
	+30	[%]	793,0	28,4%	799,5	28,6%	806,0	28,8%	812,5	29,1%	819,0	29,3%	825,5	29,5%


(4) Bifaciality Factor > 80% - Back-side power gain depends upon the specific project albedo - Efficiency is according to the surface of the module

**Mechanical Data**


Dimensions	2465 mm x 1134 mm x 30 mm
Weight	34,5 Kg
Cell Type	N-type - 156 (2 x 78 Pcs) - M10
Front Glass	2.0mm Tempered and low iron glass + ARC
Rear Side	2.0mm Tempered and low iron glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68, 3 Bypass diodes
Connector	MC4 compatible
Output cable	4mm² - Length: 1400 mm (or can be customized)

**I-V Curve**

The module relative power loss at low light irradiance of 200W/m² is less than 3%.



**Dimensions**



RECOM assumes no liability or responsibility for any typographical error, layout error, misinformation, any other error, omission, contained herein.

[www.recom-tech.com](http://www.recom-tech.com)

**Temperature Characteristics**

Pmax Temperature Coefficient	-0.30% / °C
Voc Temperature Coefficient	-0.25% / °C
Isc Temperature Coefficient	+0.046% / °C
Operating Temperature	-40~+85 °C
Nominal Operating Module Temperature (NMOT)	44 ± 2 °C

**Packing Configuration**

Container	40' HC
Pieces per Pallet	37
Pallets per Container	16
Pieces per Container	(37+37)x8=592 pcs

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to on-going innovation, research and product enhancement, RECOM Technologies reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein. Please read the safety and installation instructions before using the modules.